

English Version (Japanese Translation)

screen ink

additive

For UV ink

Additive Applications Promoting scleroticability | UV-curable type

JAR-15 Curing Accelerator

Liquid photopolymerization initiator.

Suitable for all types of UV ink.

Product Features

- Added to improve poor curing and promote curing properties.
- Made from 100% active ingredients in liquid form, it can be easily mixed, and small amounts are added for high effectiveness.

Features

hardness

Recommended Printed Materials

Material

polyester-based

Treated Polyethylene Terephthalate [PET]

Processed PET bottles

olefin-based

Treated Polyethylene [PE]

Processed PE bottles

Treated Polypropylene [PP]

Processed PP Bottles

Ethylene Vinyl Alcohol Copolymer (EVOH[®]) [EVOH]

Specifications

Lotus form

1kg Poly Bottles

100g Poly Bottles

Characteristics

liquid

How to use

- The amount of ink added is 1~3 parts per 100 parts.

Notes

- For general precautions, please refer to the attached document "[UV ink](#)". Please refer to the detailed information in the "" section.
- For safety precautions when using the product, please refer to the product's Safety Data Sheet (SDS).
- The contents provided in this information may be changed or revised without prior notice.
- When using the device, please thoroughly consider the conditions based on the evaluation results of the equipment and substrate actually being used.